



## HOLEX Pro Drill indexable drill Combination shank, 2xD, Ø DC: 14mm



### Order data

Order number	235000 14
GTIN	4062406251307
Item class	22L

### Description

#### Version:

HOLEX Pro Drill indexable drills combine cost efficiency with technically fully developed capability.

For use up to 4xD in challenging drilling applications.

**Bore tolerance:** -0.1 / +0.25 mm

#### Application:

With indexable inserts No. 235030 – 235082.

Both SOMT inserts for the outer insert seat and also XOMT inserts for the inner insert seat are required.

#### Supplied with:

With insert screws (supplied without indexable inserts).

Overhang  $L_A$ : 46 mm

Shank  $\varnothing D_s$ : 20 mm

Shank length  $L_s$ : 50 mm

Maximum adjustment limit  $V_{max}$ : 0.25 mm

ISO code indexable insert: SOMT05T204 / XOMT05T204

Pack of insert screws: 232980 1 (TX6;0.4Nm)

### Technical description

Shank length $L_s$	50 mm
Shank $\varnothing D_s$	20 mm
Series	HOLEX Pro
Number of cutting edges Z	1
Pack of insert screws	232980 1 (TX6;0.4Nm)
ISO code indexable insert	SOMT05T204 / XOMT05T204
Nominal $\varnothing D$	14
Reach $L_1$	31 mm
Overall length L	96 mm
Maximum adjustment limit $V_{max}$	0.25 mm
Overhang $L_A$	46 mm
Drill depth for indexable insert drill up to	2×D
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited cross-drilling
Use for drilling	limited drilling with oblique exit
Use for drilling	limited oblique spot drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited convexity
Through-coolant	yes
Machining strategy	HPC
Type of product	Indexable drill

## Accessories

6 mm blade for Torx® Torx® profile TX6	659922 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm

---

659957 200